ENVIRONMENTAL SITE ASSESSMENT

of a portion of
the former Hogback Mountain Ski Area
Rt. 9
Marlboro, VT
(DEC # 93-1556, UST-3)

Prepared for:

Arnold White and Richard Hamilton
Hogback Mountain Enterprises, Inc.
P.O. Box 19
Marlboro, VT 05344

Submitted By

STRATEGIC ANALYTICAL SYSTEMS, INC.
39 Square - Centennial Building
Bellows Falls, VT 05101

Dec. 12, 1994

John T. McCarthy
Manager of Operations

Steven L. Brackett
Geologist

ENVIRONMENTAL SITE ASSESSMENT
of a portion of the former
Hogback Mountain Ski Area (UST-3)
Rt. 9
Marlboro, VT

TABLE OF CONTENTS

39 SQUARE - CENTENNIAL BUILDING, BELLOWS FALLS, VT 05101
PHONE: (802) 463-0733 FAX: (802) 463-0723

BACKGROUND INFORMATION

The former Hogback Mountain Ski Area ("the site") is located on the south side of Rt. 9 in Marlboro, VT approximately four miles east of the village of Wilmington, VT. The site was operated as a ski area until 1986. On Dec. 27 and 28, 1993 four Underground Storage Tanks ("UST's") were removed from various portions of the site. All of the UST's had been out of use for more than one year and the removals were prompted by the sale of the property. Evidence of soil contamination was discovered associated with two of the four tanks during the removal. This report deals with the area around the tank identified as UST-3, a 500 gallon #2 fuel oil tank.

The UST closure report for UST- 3 was prepared by James Shippee of Vernon,VT. As indicated in the report, soil screening was performed by headspace analysis of soil samples using a Gastech OVM 1314. Results as high as 85 ppm were reported. Based on the results of the Tank Closure Report prepared by Mr. Shippee the Sites Management Section of the VT DEC requested that a Site Investigation be conducted (letter from Chuck Schwer dated 1/12/94). The objectives stated in this letter were to:

1) determine the degree and extent of contamination
2) assess the risk that the contamination possesses to potential receptors
3) develop a plan for the treatment or disposal of stockpiled contaminated soils
4) determine if there is a need for long term monitoring or remediation of soil or groundwater
5) prepare a summary report to include an area map, site plan, analytical data, well logs, groundwater contour map and conclusions and recommendations.

SCOPE OF WORK PERFORMED

Installation of Soil Borings

On September 26, 1994 Strategic Analytical Systems, Inc. oversaw the installation of 21 soil borings at the site. The soil borings were installed by Green Mountain Boring of Barre, VT. Soil samples were collected continuously from the surface to total depth using a 24" split spoon sampler and were field screened for Volatile Organic Compounds ("VOC's") by headspace analysis using a Gastech 1314 OVM. Soil types and conditions were recorded and logs were prepared for the soil borings SB-1 through SB-4. These logs are included in the Appendices of this report.

Results of Field Screening of Soil Samples

Below is a table which contains the results of the field screening performed on soil samples

39 SQUARE - CENTENNIAL BUILDING, BELLOWS FALLS, VT 05101
PHONE: (802) 463-0733 FAX: (802) 463-0723

collected from P1 through P17 and SB-1 through SB-3. Field screening was performed using a Gastech OVM calibrated to 400 ppm hexane. As the attached boring logs show, the soil section was thin and consisted primarily of an A layer (topsoil) and a B layer (clay loam). Thicknesses varied but on average the A layer was 6" thick and the B layer was 30" to 40" thick. None of the soil borings encountered groundwater although there was evidence of a seasonal high water table in the bottom 6 to 12" of the soil borings southeast of the former location of UST-3. Petroleum smell and OVM response were evident in the soil samples taken from two soil borings: SB-2 and P5. As can be seen from the Site Plan both were immediately adjacent to the former location of UST-3.

	0 -2' sample	2' - 4' sample	4' - 6' sample
P-1	ND	ND	NS
P-2	ND	ND	NS
P-3	ND	ND	NS
P-4	ND	NS	NS
P-5	ND	**10 ppm**	NS
P-6	ND	ND	NS
P-7	ND	NS	NS
P-8	ND	ND	NS
P-9	ND	ND	NS
P-10	ND	ND	NS
P-11	ND	ND	NS
P-12	ND	ND	ND
P-13	ND	ND	ND
P-14	ND	ND	NS
P-15	ND	ND	NS
P-16	ND	ND	ND
P-17	ND	ND	ND
SB-1	ND	ND	ND

39 SQUARE - CENTENNIAL BUILDING, BELLOWS FALLS, VT 05101
PHONE: (802) 463-0733 FAX: (802) 463-0723

SB-2	ND	ND	**35 ppm**
SB-3	ND	ND	ND

SOURCE OF CONTAMINATION

Based on the Site Assessment report for this site and the work conducted for this study it is the opinion of Strategic Analytical Systems, Inc. that the soil contamination which exists at the site is the result of leakage from UST-3 which was removed on December 28, 1993.

RECEPTOR ANALYSIS

Potential receptors of the contamination present at Hogback Mountain consist of one building adjacent to the site, soils and the drinking water supply for this site.

The adjacent building, the Marlboro Inn, is located upgradient to the former location of UST-3 and is outside of the defined area of soil contamination. The Marlboro Inn does have a basement which was inspected visually and was screened for VOC's. There was no visual evidence of contamination in the basement and the results of the air sample screening for VOC's were negative.

As stated above, leakage from UST-3 has impacted a certain amount of soil at the site. The areal extent of the soil contamination is shown on the Contaminant Isopleth Map in the Appendices of this report.

The water supply for this site is a private drinking water well located approximately 3100' northwest of the former location of UST-3. On February 1, 1994 a drinking water sample was collected from the water supply for the site and sent to Eastern Analytical of Concord, NH for analysis for VOC's by EPA Method 524. All results were negative. A copy of the results is included in the Appendices of this report.

SITE GEOLOGY AND HYDROGEOLOGY

The Hogback Mountain site is located along the eastern ridges of the Green Mountains of southern Vermont. Bedrock in the area consists of the Cambo-Ordovician Stowe formation and the Ordovician Missisquoi formation. Subsurface investigations of the site indicate that the soil thicknesses in the area range from 6" to 6' and consist of the upland Rawsonville-Hogback series. These soils are characterized as shallow, well drained sandy loams. No groundwater was encountered during the installation of soil borings.

39 SQUARE - CENTENNIAL BUILDING, BELLOWS FALLS, VT 05101
PHONE: (802) 463-0733 FAX: (802) 463-0723

CONCLUSIONS

Based on the data collected in this Site Investigation Strategic Analytical Systems, Inc. concludes the following:

- Soil screening results for samples from P-5 and SB-1 indicate that a release of #2 fuel oil did result in a small amount of soil contamination at the site. Approximately two yds.^{3} of contaminated soil was excavated during the removal of UST-3. This soil remains stockpiled at the site.

- There appears to be a very small volume (< 4 yds.^{3}) of unexcavated soil which contains # 2 fuel oil in concentrations greater that the 10 ppm standard set out in the Vermont Agency of Natural Resources Guidelines for Handling Petroleum Contaminated Soil and Carbon Media.

- It does not appear that groundwater has been impacted in that groundwater was not encountered, and there was no evidence of a seasonal high water table, in the defined area of soil contamination.

- As of the date of this report this contamination had not yet impacted any potential receptors.

RECOMMENDATIONS

In light of the conclusions set out above Strategic Analytical Systems, Inc. recommends that;

- All contaminated soils be excavated and disposed of offsite. Once removal and disposal has been completed the site should be removed from the active sites list.

LIMITATIONS

The findings set forth in this report are strictly limited in time and scope to the date of evaluation. The conclusions presented are based solely on the services described herein and not on scientific tasks or procedures beyond the scope of agreed upon services.

WP51\document\hogback3.01r

39 SQUARE - CENTENNIAL BUILDING, BELLOWS FALLS, VT 05101
PHONE: (802) 463-0733 FAX: (802) 463-0723



Sunderland
Arlington
East Arlington
Chiselville
Kelley Stand
Stratton
Wardsboro
West Wardsboro
South Wardsboro
Jamaica
East Jamaica
West Townshend
Townshend
Harmony-ville
Simpsonville
Westminster West
Brookline
Newfane
Landmark College
East Putney
Putney
Connecticut
Shaftsbury
Shaftsbury Center
South Shaftsbury
White Creek
NATIONAL
FOREST
WINDHAM
Glastenbury Mtn. 3748
Somerset Reservoir
Mt. Snow Ski Area
Mount Snow
East Dover
Dover
Williamsville
Brookside
South Newfane
West Dummerston
Dummerston Cen.
East Dummerston
Maple Valley Ski Area
Dutton Pines State Park
Spofford Lake
Bald Mountain 2857
Red Mill Brook Rec. Area
Haystack Mtn. 3420
Haystack Mtn. Ski Area
Bennington
(See Inset)
Bennington College
McCullough Mansion
Searsburg
Woodford
Woodford State Park
Prospect Mtn. Ski Area
Prospect Mtn. 2767
Harmon Hill 2320
Old Bennington
Mt. Anthony 2340
Southern Vermont College
NEW YORK
Hoosick
Wilmington
Hogback Mtn. 2410
Mount Olga
Molly Stark St. Park
Hogback Mtn. Ski Area
Marlboro
Marlboro College
West Brattleboro
Brattleboro
(See Inset)
Sunset Lake
South Pond
Gates Pond
Harriman Reservoir
Heartwellville
North Pownal
Pownal Center
Pownal
Green Mountain Park
The Dome 2748
Stamford
Readsboro Falls
Readsboro
Whitingham
Jacksonville
Brigham Young Mem.
West Halifax
Halifax
Green River
Weatherhead Hollow Pd.
Guilford
West Guilford
Guilford Center
Fort Dummer State Park
Vernon
Central Park
Welcome Center
NEW HAMPSHIRE
MASSACHUSETTS
Williamstown
N. Adams
Sadawga Pond
Sherman Res.
Monroe Bridge
North Bernardston
Springfield
Pittsfield
C
D
E
F
G

HOGBACK ENTERPRISES
MARLBORO, VERMONT



500 Gallon #2 Fuel Oil Tank

UST #3



UST #3

500 GALLON: #2 FUEL OIL TANK


Site Water Supply Source
Site

Green Mountain Boring Co., Inc.

R. D. 2 — BARRE, VERMONT 05641

SHEET 10 OF 15
DATE 9-26-94
HOLE NO. P-1 — P-8
LINE & STA.
OFFSET

TO Stratigic Analytical Sys. ADDRESS Bellows Falls, VT
PROJECT NAME Hogback Enterprises LOCATION Marlboro, VT
REPORT SENT TO S.A.S.I. PROJ. NO.
SAMPLES SENT TO S.A.S.I. OUR JOB NO. 94-11[illegible]

GROUND WATER OBSERVATIONS

At ..... at ..... Hours

At ..... at ..... Hours

	CASING	SAMPLER	CORE BAR.
Type	AUGERS	SPLIT SPOON	
Size I. D.	Solid Augers	3"	
Hammer Wt.		140#	
Hammer Fall		30"	

SURFACE ELEV.
DATE STARTED 9-26-94
DATE COMPL. 9-26-94
BORING FOREMAN
INSPECTOR Steve Brackett
SOILS ENGR.

LOCATION OF BORING:

DEPTH	Casing Blows per foot	Sample Depths From — To	Type of Sample	Blows per 6" on Sampler From — To 0-6	6-12	12-18	Moisture Density or Consist.	Strata Change Elev.	SOIL IDENTIFICATION Remarks include color, gradation, Type of soil etc. Rock-color, type, condition, hardness, Drilling time, seams and etc.	SAMPLE No.	Pen	Rec.
		P-1		Fine sand and silt					Auger refusal on stone at 3'4" - No water No petroleum oder		3'4"	
		P-2		Fine sand and silt					Auger refusal on stone at 3'10" - No water No petroleum oder		3'10"	
		P-3		Fine sand and silt					Auger refusal on stone at 3'4" - No Water No petroleum oder		3'4"	
		P-4		Fine sand and silt					Auger refusal on stone at 2' - No water No petroleum oder		2'	
		P-5		Fine sand and silt					Auger refusal on stone at 4'5" - No water Slight Petroleum oder		4'5"	
		P-6		Fine sand and silt					Auger refusal on stone at 4'8" - No water No petroleum oder		4'8"	
		P-7		Fine sand and silt					Auger refusal on stone at 2'9" - No water No petroleum oder		2'9"	
		P-8		Fine sand and silt few pebbles					Auger refusal on stone at 4'3" - No water No petroleum oder		4'3"	

GROUND SURFACE TO ..... USED ..... AUGERS: THEN .....

Sample Type
D = Dry C = Cored W = Washed
UP = Undisturbed Piston
TP = Test Pit A = Auger V = Vane Test
UT = Undisturbed Thinwall

Proportions Used
trace 0 to 10%
little 10 to 20%
some 20 to 35%
and 35 to 50%

140 lb. Wt. x 30" fall an 2" O. D. Sampler

Cohesionless Density
0-10 Loose
10-30 Med. Dense
30-50 Dense
50 + Very Dense

Cohesive Consistency
0-4 Soft
4-8 M/Stiff
8-15 Stiff
15-30 V-Stiff
30 + Hard

SUMMARY:
Earth Boring
Rock Coring
Samples

HOLE NO.

Green Mountain Boring Co., Inc.

R. D. 2 — BARRE, VERMONT 05641

SHEET 11 OF 15

TO Stratigic Analytical Sys. ADDRESS Bellows Falls, VT

PROJECT NAME Hogback Enterprises LOCATION Marlboro, VT

REPORT SENT TO S.A.S.I. PROJ. NO.

SAMPLES SENT TO S.A.S.I. OUR JOB NO. 94-116

DATE 9-26-94

HOLE NO. P-9 - P-16

LINE & STA.

OFFSET

GROUND WATER OBSERVATIONS

At ..... at ..... Hours

At ..... at ..... Hours

	CASING	SAMPLER	CORE BAR.
Type	AUGERS	SPLIT SPOON	
Size I. D.	Solid Augers 3 1/8"		
Hammer Wt.		140#	
Hammer Fall		30"	

SURFACE ELEV.

DATE STARTED 9-26-94

DATE COMPL.

BORING FOREMAN Lawrence

INSPECTOR Steve Brackett

SOILS ENGR.

LOCATION OF BORING:

DEPTH	Casing Blows per foot	Sample Depths From — To	Type of Sample	Blows per 6" on Sampler From 0-6	6-12	To 12-18	Moisture Density or Consist.	Strata Change Elev.	SOIL IDENTIFICATION Remarks include color, gradation, Type of soil etc. Rock-color, type, condition, hardness, Drilling time, seams and etc.	SAMPLE No.	Pen	Rec.
		P-9		Fine sand and silt					Auger refusal on stone at 3' soil is moist3' No petroleum oder		3'	
		P-10		Fine sand and silt					Auger refusal on stone at 4' soil is moist 4' No petroleum oder		4'	
		P-11		Fine sand and silt					Auger refusal on stone at 4'4" soil is moist 4'4" No petroleum oder		4'4"	
		P-12		Fine sand and silt					Auger refusal on stone at 5'1" soil is moist 5'1" No petroleum oder		5'1"	
		P-13		Fine sand and silt					Auger refusal on stone at 5'5" Soil is moist No petroleum oder		5'5"	
		P-14		Fine sand and silt Silt with traces of fine sand at 2'6"					Auger refusal on stone at 3' soil is moist at 2'6" No petroleum oder		3'	
		P-15							Auger refusal on stone at 4' Soil is moist No petroleum oder		4'	
		P-16		Fine sand and silt					Auger refusal on stone at 5'4"		5'4"	

Line 3

Line 4

GROUND SURFACE TO USED AUGERS: THEN

140 lb. Wt. x 30" fall an 2" O. D. Sampler

Sample Type

D = Dry C = Cored W = Washed

UP = Undisturbed Piston

TP = Test Pit A = Auger V = Vane Test

UT = Undisturbed Thinwall

Proportions Used

trace	0 to 10%
little	10 to 20%
some	20 to 35%
and	35 to 50%

Cohesionless Density

0-10	Loose
10-30	Med. Dense
30-50	Dense
50 +	Very Dense

Cohesive Consistency

0-4	Soft
4-8	M/Stiff
8-15	Stiff
15-30	V-Stiff
30 +	Hard

SUMMARY:

Earth Boring

Rock Coring

Samples

HOLE NO.

Green Mountain Boring Co., Inc.

R. D. 2 — BARRE, VERMONT 05641

SHEET 12 OF 15
DATE 9-26-94
HOLE NO. P-17
LINE & STA.
OFFSET

TO Stratigic Analytical Sys. ADDRESS Bellows Falls, VT
PROJECT NAME Hogback Enterprises LOCATION Marlboro, VT
REPORT SENT TO S.A.S.I. PROJ. NO.
SAMPLES SENT TO S.A.S.I. OUR JOB NO. 94-11[illegible]

GROUND WATER OBSERVATIONS

At ..... at ..... Hours

At ..... at ..... Hours

	CASING	SAMPLER	CORE BAR.
Type	AUGERS	SPLIT SPOON	
Size I. D.	Solid AUgers	1 3/8"	
Hammer Wt.		140#	
Hammer Fall		30"	

SURFACE ELEV.
DATE STARTED 9-26-94
DATE COMPL. 9-26-94
BORING FOREMAN Lawrence
INSPECTOR Steve Brackett
SOILS ENGR.

LOCATION OF BORING:

DEPTH	Casing Blows per foot	Sample Depths From — To	Type of Sample	Blows per 6" on Sampler From 0-6	6-12	To 12-18	Moisture Density or Consist.	Strata Change Elev.	SOIL IDENTIFICATION Remarks include color, gradation, Type of soil etc. Rock-color, type, condition, hardness, Drilling time, seams and etc.	SAMPLE No.	Pen	Rec.
		P-17		Fine sand and silt					Auger refusal on stone at 6'8" soil is moist 6'8" No petroleum oder	1	6"	8"

GROUND SURFACE TO ..... USED ..... AUGERS: THEN .....

Sample Type
D = Dry C = Cored W = Washed
UP = Undisturbed Piston
TP = Test Pit A = Auger V = Vane Test
UT = Undisturbed Thinwall

Proportions Used
trace 0 to 10%
little 10 to 20%
some 20 to 35%
and 35 to 50%

140 lb. Wt. x 30" fall an 2" O. D. Sampler

Cohesionless Density		Cohesive Consistency		
0-10	Loose	0-4	Soft	30 + Hard
10-30	Med. Dense	4-8	M/Stiff	
30-50	Dense	8-15	Stiff	
50 +	Very Dense	15-30	V-Stiff	

SUMMARY:
Earth Boring
Rock Coring
Samples

HOLE NO.

Green Mountain Boring Co., Inc.

R. D. 2 — BARRE, VERMONT 05641

SHEET 13 OF 15

TO Stratigic Analytical Sys. ADDRESS Bellows Falls, VT

PROJECT NAME Hogback Mt. Enterpri LOCATION Marlboro, VT

REPORT SENT TO S.A.S.I. PROJ. NO.

SAMPLES SENT TO S.A.S.I. OUR JOB NO. 94-116

DATE 9-26-94

HOLE NO. SB-1

LINE & STA.

OFFSET None

GROUND WATER OBSERVATIONS

At None at 1 Hours

At ..... at ..... Hours

	CASING	SAMPLER	CORE BAR.
Type	AUGERS	SPLIT SPOON	
Size I. D.	AW Rod	1 3/8"	
Hammer Wt.		140#	
Hammer Fall		30"	

SURFACE ELEV.

DATE STARTED 9-26-94

DATE COMPL. 9-26-94

BORING FOREMAN Lawrence

INSPECTOR Steve Brackett

SOILS ENGR.

LOCATION OF BORING: As shown by inspector - Down grade of tank pit

DEPTH	Casing Blows per foot	Sample Depths From — To	Type of Sample	Blows per 6" on Sampler From 0-6	6-12	To 12-18	Moisture Density or Consist.	Strata Change Elev.	SOIL IDENTIFICATION Remarks include color, gradation, Type of soil etc. Rock-color, type, condition, hardness, Drilling time, seams and etc.	SAMPLE No.	Pen	Rec.
		0'-2'	Dry	2 2	2	3	Dry		Topsoil into a fine sand with silt organics	1	24"	18"
		2'-4'	Dry	4 23	4	4	Dry		Fine sand with small stones	2	24"	15"
		4'-4'9"	Dry	37	100	for 3"	Dry		Fine sand with small stones into weathered bedrock Split spoon refusal	3	9"	8"

GROUND SURFACE TO 4'9" USED AW Rod AUGERS: THEN Split spoon refusal on stone

Sample Type
D=Dry C=Cored W=Washed
UP=Undisturbed Piston
TP=Test Pit A=Auger V=Vane Test
UT=Undisturbed Thinwall

Proportions Used
trace 0 to 10%
little 10 to 20%
some 20 to 35%
and 35 to 50%

140 lb. Wt. x 30" fall an 2" O. D. Sampler

Cohesionless Density		Cohesive Consistency		
0-10	Loose	0-4	Soft	30 + Hard
10-30	Med. Dense	4-8	M/Stiff	
30-50	Dense	8-15	Stiff	
50 +	Very Dense	15-30	V-Stiff	

SUMMARY:
Earth Boring 4'9"
Rock Coring
Samples 3

HOLE NO. SB-1

Green Mountain Boring Co., Inc.

R. D. 2 – BARRE, VERMONT 05641

SHEET 15 OF 15
DATE 9-26-94
HOLE NO. SB-3
LINE & STA.
OFFSET None

TO Stratigic Analytical Sys. ADDRESS Bellows Falls, VT
PROJECT NAME Hogback Enterprises LOCATION Marlboro, VT
REPORT SENT TO S.A.S.I. PROJ. NO.
SAMPLES SENT TO S.A.S.I OUR JOB NO. 94-115

GROUND WATER OBSERVATIONS
At None at 0 Hours
At ..... at ..... Hours

	CASING	SAMPLER	CORE BAR.
Type	AUGERS	SPLIT SPOON	
Size I. D.	AW Rod	1 3/8"	
Hammer Wt.		140#	
Hammer Fall		30"	

SURFACE ELEV.
DATE STARTED 9-26-94
DATE COMPL. 9-26-94
BORING FOREMAN Lawrence
INSPECTOR Steve Brackett
SOILS ENGR.

LOCATION OF BORING: As shown by inspector - down grade of tank pit

DEPTH	Casing Blows per foot	Sample Depths From – To	Type of Sample	Blows per 6" on Sampler From 0-6	6-12	To 12-18	Moisture Density or Consist.	Strata Change Elev.	SOIL IDENTIFICATION Remarks include color, gradation, Type of soil etc. Rock-color, type, condition, hardness, Drilling time, seams and etc.	SAMPLE No.	Pen	Rec.
		0'-2'	Dry	2	2	3	Dry		Topsoil into a fine sand and silt	1	24"	12"
				4								
		2'-4'	Dry	2	2	2	Moist		Fine sand and silt	2	24"	18"
				4								
		4'-5'6"	Dry	24	36	50	Dry		Fine sand and silt	3	18"	18"
									Split spoon refusal on stone			

GROUND SURFACE TO 5'6" USED AW Rod AUGERS: THEN Split spoon refusal

Sample Type
D = Dry C = Cored W = Washed
UP = Undisturbed Piston
TP = Test Pit A = Auger V = Vane Test
UT = Undisturbed Thinwall

Proportions Used
trace 0 to 10%
little 10 to 20%
some 20 to 35%
and 35 to 50%

140 lb. Wt. x 30" fall an 2" O. D. Sampler

Cohesionless Density		Cohesive Consistency		
0-10	Loose	0-4	Soft	30 + Hard
10-30	Med. Dense	4-8	M/Stiff	
30-50	Dense	8-15	Stiff	
50 +	Very Dense	15-30	V-Stiff	

SUMMARY:
Earth Boring 5'6"
Rock Coring
Samples 3

HOLE NO. SB-3

COPY

LABORATORY REPORT

Eastern Analytical, Inc. ID#: 7805* SAS

Client: Strategic Analytical Systems
Client Designation: **HOG-CM-001/Hogback Enterprises**

Sample Qty/Type: 1 aqueous
Date Received: February 1, 1994

Hazardous Substance List Volatile Organic Compounds

Sample ID:	HOG-CM-001
Matrix:	Aqueous
Date of Analysis:	2/1/94
Units:	µg/L
Analyst:	NZ
Method:	EPA 624
Benzene	< 0.5
Bromobenzene	< 0.5
Bromochloromethane	< 0.5
Bromodichloromethane	< 0.5
Bromoform	< 0.5
Bromomethane	<2
n-Butylbenzene	< 0.5
sec-Butylbenzene	< 0.5
tert-Butylbenzene	< 0.5
Carbon tetrachloride	< 0.5
Chlorobenzene	< 0.5
Chloroethane	<2
Chloroform	< 0.5
Chloromethane	<2
2-Chlorotoluene	< 0.5
4-Chlorotoluene	< 0.5
Dibromochloromethane	< 0.5
1,2-Dibromo-3-chloropropane	< 0.5
1,2-Dibromoethane	< 0.5
Dibromomethane	< 0.5
1,2-Dichlorobenzene	< 0.5
1,3-Dichlorobenzene	< 0.5
1,4-Dichlorobenzene	< 0.5
Dichlorodifluoromethane	<2
1,1-Dichloroethane	< 0.5
1,2-Dichloroethane	< 0.5
1,1-Dichloroethene	< 0.5
cis-1,2-Dichloroethene	< 0.5
trans-1,2-Dichloroethene	< 0.5
1,2-Dichloropropane	< 0.5
1,3-Dichloropropane	< 0.5
2,2-Dichloropropane	< 0.5
1,1-Dichloropropene	< 0.5
Ethylbenzene	< 0.5
Hexachlorobutadiene	< 0.5

Approved By: Timothy Schaper, Organics Supervisor Timothy D. Schaper

LABORATORY REPORT

Eastern Analytical, Inc. ID#: 7805' SAS

Client: Strategic Analytical Systems
Client Designation: **HOG-CM-001/Hogback Enterprises**

Sample Qty/Type: 1 aqueous
Date Received: February 1, 1994

Hazardous Substance List Volatile Organic Compounds

Sample ID:	HOG-CM-001
Matrix:	Aqueous
Date of Analysis:	2/1/94
Units:	µg/L
Analyst:	NZ
Method:	EPA 524
Isopropylbenzene	< 0.5
p-Isopropyltoluene	< 0.5
Methylene chloride	< 0.5
Naphthalene	< 0.5
n-Propylbenzene	< 0.5
Styrene	< 0.5
1,1,1,2-Tetrachloroethane	< 0.5
1,1,2,2-Tetrachloroethane	< 0.5
Tetrachloroethene	< 0.5
Toluene	< 0.5
1,2,3-Trichlorobenzene	< 0.5
1,2,4-Trichlorobenzene	< 0.5
1,1,1-Trichloroethane	< 0.5
1,1,2-Trichloroethane	< 0.5
Trichloroethene	< 0.5
Trichlorofluoromethane	<2
1,2,3-Trichloropropane	< 0.5
1,2,4-Trimethylbenzene	< 0.5
1,3,5-Trimethylbenzene	< 0.5
Vinyl chloride	<2
o-Xylene	< 0.5
m,p-Xylene	< 0.5

Approved By: Timothy Schaper, Organics Supervisor